Nature-Pavé

PRODUITS POUR LE BÉTON

Acry-Bar

Fiche Technique : *Acry-Bar* est un produit acrylique à haute teneur en solide, qui scelle les bétons et terrazzos sans les désagréments des solvants organiques volatiles. Il les protège contre l'eau, les sels de déglaçage, les huiles. Il élimine les poussières générées par les surfaces de béton à forte circulation.

Mode d'emploi : Nettoyer la surface pour enlever les sels, graisses, pellicules et vernis existants autres qu'*Acry-Bar*. Pour les surfaces fraîchement bétonnées, attendre au moins 14 jours, puis laver avec du *Efflo-Clean-Green* de Nature Pavé. Recommencer le lavage au besoin, jusqu'à ce que la surface ne présente plus d'efflorescence blanche.

Bien agiter. Utiliser un rouleau, pinceau, brosse à poils mous ou linge de coton, puis appliquer une couche uniforme. Laisser sécher 60 minutes.

Base à l'eau	**21% d'acrylique solide**
Selon l'absorption; couvre environ	**500 pieds^2/US gal ou 46m^2/4L**

Finition : Appliquer directement le fini acrylique ***Acry-Linker*** sur le scellant ***Acry-Bar***, pour un fini durable et lustré des planchers de béton et terrazzo à circulation dense.

Garantie : La responsabilité du fabriquant se limite au remplacement du produit avec preuve d'achat. Le fabriquant n'est pas responsable des dommages corporels et matériels que pourraient causer ce produit.

Ce produit ne génère pas de déchet hautement dangereux ou toxique.

Précautions : Garder hors de la portée des enfants, peut irriter la peau et les yeux, ne pas ingérer. Porter des gants lors de l'application, rincer à l'eau pendant au moins 15 minutes en cas de réaction avec la peau ou éclaboussures dans les yeux. Si les douleurs persistent demander de l'aide médicale. En cas d'ingestion, ne pas faire vomir et demander immédiatement de l'aide médicale.

Nature-Pavé

PRODUCTS FOR CONCRETE

Acry-Bar

Technical data sheet : *Acry-Bar* is an acrylic resin with high solid content, which seals the concrete and terrazzo without the inconvenience of volatile organic solvents. It protects against water, salts, oil. It eliminates the dust created by concrete surfaces with high traffic.

Instructions: Clean the surface to remove the salts, greases, film and varnish other than *Acry-Bar*. For fresh concrete, wait at least 14 days, then wash the surface with *Efflo-Clean-Green* from Nature Pavé diluted to an equivalent amount of water. Repeat the washing if necessary, until the surface has no longer white efflorescence after drying.

Shake well. Use a soft bristle brush or cotton cloth, then apply an even layer. Allow to dry 60 minutes.

Water based	**21% d'acrylique solide**
Porosity dependent; covers approx.	**500 feet^2/US gal or 46m^2/4L**

Finish: Apply directly the acrylic finish ***Acry-Linker*** on the ***Acry-Bar*** sealer for a durable and high gloss concrete or terrazzo surface.

Warranty: The manufacturer's liability is limited to replacement of the product with proof of purchase. The manufacturer is not liable for injury or damage that could cause this product.

This product does not generate highly toxic or hazardous waste.

Caution: Keep out of the reach of children , can irritate the skin and eyes, do not ingest. Wear gloves when applying, rinse with water for at least 15 minutes in case of reaction with the skin or splashed in the eyes. If pain persists seek medical help. If swallowed, do not induce vomiting and seek immediate medical assistance.